

PRODUCT DATA SHEET

Reviewed 01/02/2016



YOU CAN'T BUY A BETTER PAINT FOR LESS!™



Wood Primer

SECTION A:	DESCRIPTION High quality general purpose primer for new interior and exterior wooden surfaces with good flow and leveling properties. Provides excellent adhesion to wood to allow subsequent top-coats to be applied.
SECTION B:	COMPOSITION Alkyd resin in Hydrocarbon solvent
SECTION C:	PHYSICAL PROPERTIES Colour: Pink, White Appearance: Matt Viscosity: 70 - 80 Ku @ 25°C Shelf Life: 12 Months Storage Conditions: Normal Pack Size: 1L, 5L, 20L S.G.: 1.41 - 1.46kg/L Solids Mass: 64 - 69% Solids Volume: 39 - 44%
SECTION D:	APPLICATION PROPERTIES Method: Brush, Roller or Airless Spray Average Dft: 45 microns (Recommended) Spreading Rate: 8 - 10 m ² /L (depending on the porosity) Wet Film Thickness: 60 - 80 microns Number of coats: 1 - 2 or as required Drying Time: Surface 3 - 4hrs, hard 16hrs max Overcoating Time: Between 16 - 72hrs Thinning: Not Applicable Cleaning Solvent: Excelsior Turps Recommended systems: As a primer or undercoat as per manufacturer's instructions.
SECTION E:	APPLICATION METHOD The product is ready for use but, it can be thinned with 10% MINERAL TURPENTINE to ensure better penetration into the wood. One coat application is normally sufficient but two coats can be applied if necessary. NEW WOOD - Knots must be prepared with WOOD KNOTTING. - Spot prime nail heads with appropriate primer. - Special attention must be given to painting the end grain to avoid moisture penetration. Do not if there is any moisture in the wood or in wet weather.
SECTION F:	PRECAUTION Flash point: Below 24°C Toxicity: Normal when used in well ventilated areas
SECTION G:	NOTE No guarantees are implied by the recommendations contained herein; since the data sheet is issued for information only. Method of application, surface cleanliness, conditions of use etc. are beyond our control.